

Ś

SMART-30S is Value for Everyone!

www.smartidcardprinter.com



Applications

- ID / Membership
- Access control / Security
- Healthcare
- Government
- Banking Card
- Transportation
- Retail
- Gift / Promotion / Loyalty

Features

- Color & Mono Printing
- Transparent Card with Magnetic Stripe
- Full Encoding Support
- (Magnetic, Contact, Contactless)
- Removable Stacker
- Compact Size

- Overlay 🔸
- UV Panel
- 300dpi & Edge-to-Edge 🔸
 - Contact
 - Contactless
 - Magnetic Stripe 🔸

SMART-30S Specifications

PrintingPrint Type> Dye-SublimationPrint AreaEdge to EdgeResolution300 dpiDual Side Printing> TBDCard-Card Feeding> AutomaticCard Size> ISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness> 0.38mm(15mil) ~ 0.76mm(30mil)Card Type> PVC, Composite PVC, PETPrint Speed-Monochrome> 5 sec. (720 cards/hour)YMCKO> 28 sec. (128 cards/hour)Capacity-Input Hooper> 80 cardsOutput Hooper> 25 cardsSystem-Memory> 644MB RAMControl Panel> LED ButtonSupported Platforms> Microsoft Windows 20002003/XP/Vistal7, Mac OS, LinuxCommunication> USB, Ethernet (Option)Power Consumption (Max)48WTemperature / Humidity> 172 mm x 377mm x 190mmWeight> 3.4 kg / 7.5 lbsEncoding Options-MagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)			SMART-30S (Single Side Card Printer
Print TypeDye-SublimationPrint AreaEdge to EdgeResolution300 dpiDual Side PrintingTBDCard FeedingAutomaticCard FieldISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness0.38mm(15mil) ~ 0.76mm(30mil)Card TypePVC, Composite PVC, PETPrint SpeedMonochromeMonochrome5 sec. (720 cards/hour)YMCKO28 sec. (128 cards/hour)CapacityInput HooperInput Hooper80 cardsOutput Hooper80 cardsOutput Hooper164MB RAMControl PanelLED ButtonSupported PlatformsMicrosoft Windows 20002003XPIVistal7, Mac OS, LinuxCommunicationUSB, Ethernet (Option)Power Consumption (Max)48WTemperature / Humidity15~35°C / 20~80%DimensionsIso 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)	Printing		
Print AreaEdge to EdgeResolution $300 dpi$ Dual Side PrintingTBDCard-Card Feeding $Automatic$ Card Size $ISO CR80 (54mm x 86mm / 2.12" x 3.38")$ Card Thickness $0.38mm (15mil) \sim 0.76mm (30mil)$ Card Type $PVC, Composite PVC, PET$ Print Speed-Monochrome $5 \sec. (720 cards/hour)$ YMCKO $28 \sec. (128 cards/hour)$ Capacity-Input Hooper $80 cards$ Output Hooper $25 cards$ System-Memory $64MB RAM$ Control PanelLED ButtonSupported PlatformsMicrosoft Windows 20002003/XP/Vista/7, Mac OS, LinuxCommunicationUSB, Ethernet (Option)Power Consumption (Max) $48W$ Temperature / Humidity $15-35 {}^{\circ}C / 20-80\%$ Dimensions-Dimensions (W x L x H) $172 mm x 377 mm x 190 mm$ Weight $3.4 kg / 7.5 lbs$ Encoding Options-MagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)(Internal & External)ISO 15693, DESFIRE, ICLASS		•	Dye-Sublimation
Resolution $:$ 300 dpiDual Side Printing $:$ TBDCardCard Feeding $:$ AutomaticCard Size $:$ ISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness $:$ $:$ Card Type $:$ PVC, Composite PVC, PETPrint SpeedMonochrome $:$ $:$ SystemInput Hooper $:$ $:$ Memory $:$ $:$ Print Speed $:$ Memory $:$ $:$ <td></td> <td></td> <td> [/ / / /</td>			[/ / / /
CardCard Feeding• AutomaticCard Size• ISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness• 0.38mm(15mil) ~ 0.76mm(30mil)Card Type• PVC, Composite PVC, PETPrint SpeedMonochrome• 5 sec. (720 cards/hour)YMCKO• 28 sec. (128 cards/hour)CapacityInput Hooper• 80 cardsOutput Hooper• 80 cardsOutput Hooper• 80 cardsOutput Hooper• 64MB RAMControl Panel• LED ButtonSupported Platforms• Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions•Dimension (W × L × H)• 172 mm x 377mm x 190mmWeight• 3.4 kg/7.5 lbsEncoding Options•Magnetic• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), (Internal & External)Iso 15693, DESFIRE, iCLASS	Resolution		300 dpi
Card Feeding· AutomaticCard Size· ISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness· 0.38mm(15mil) ~ 0.76mm(30mil)Card Type· PVC, Composite PVC, PETPrint Speed·Monochrome· 5 sec. (720 cards/hour)YMCKO· 28 sec. (128 cards/hour)YMCKO· 28 sec. (128 cards/hour)Capacity·Input Hooper· 80 cardsOutput Hooper· 80 cardsOutput Hooper· 64MB RAMControl Panel· LED ButtonSupported Platforms· Microsoft Windows 2000/2003XP/Vista/7, Mac OS, LinuxCommunication· USB, Ethernet (Option)Power Consumption (Max)· 48WTemperature / Humidity· 15~35 °C / 20~80%Dimensions·Dimension (W x L x H)· 172 mm x 377mm x 190mmWeight· 3.4 kg / 7.5 lbsEncoding Options·Magnetic· ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard· ISO 7816 (ID -1)Contactless Smartcard· MIFARE, ISO 14443 (Type A / B), (Internal & External)Ionension & Strengen (Internal)· So 15693, DESFIRE, iCLASS	Dual Side Printing		ТВД
Card SizeISO CR80 (54mm x 86mm / 2.12" x 3.38")Card Thickness $0.38mm(15mil) \sim 0.76mm(30mil)$ Card Type PVC , Composite PVC, PETPrint Speed	Card		
Card Thickness0.38mm(15mil) ~ 0.76mm(30mil)Card TypePVC, Composite PVC, PETPrint SpeedMonochrome5 sec. (720 cards/hour)YMCKO28 sec. (128 cards/hour)CapacityInput Hooper80 cardsOutput Hooper25 cardsSystemMemory64MB RAMControl PanelLED ButtonSupported PlatformsMicrosoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunicationUSB, Ethernet (Option)Power SupplyFree Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)48WTemperature / Humidity15~35 °C / 20~80%DimensionsJimensionsDimension (W x L x H)172 mm x 377mm x 190mmWeight3.4 kg/7.5 lbsEncoding OptionsIIOMagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)	Card Feeding		Automatic
Card TypePVC, Composite PVC, PETPrint SpeedMonochrome• 5 sec. (720 cards/hour)YMCKO• 28 sec. (128 cards/hour)CapacityInput Hooper• 80 cardsOutput Hooper• 80 cardsOutput Hooper• 25 cardsSystemMemory• 64MB RAMControl Panel• LED ButtonSupported Platforms• Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions	Card Size		ISO CR80 (54mm x 86mm / 2.12" x 3.38")
Print SpeedMonochrome• 5 sec. (720 cards/hour)YMCKO• 28 sec. (128 cards/hour)Capacity	Card Thickness		0.38mm(15mil) ~ 0.76mm(30mil)
Monochrome5 sec. (720 cards/hour)YMCKO28 sec. (128 cards/hour)CapacityInput Hooper0utput Hooper25 cardsSystemMemory64MB RAMControl PanelLED ButtonSupported PlatformsMicrosoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunicationPower SupplyFree Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)48WTemperature / Humidity15~35 °C / 20~80%DimensionsDimensionsDimension (W x L x H)NagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)	Card Type		PVC, Composite PVC, PET
Monochrome5 sec. (720 cards/hour)YMCKO28 sec. (128 cards/hour)CapacityInput Hooper0utput Hooper25 cardsSystemMemory64MB RAMControl PanelLED ButtonSupported PlatformsMicrosoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunicationPower SupplyFree Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)48WTemperature / Humidity15~35 °C / 20~80%DimensionsDimensionsDimension (W x L x H)NagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), (Internal & External)	Print Speed		
Capacity			5 sec. (720 cards/hour)
Input Hooper•80 cardsOutput Hooper•25 cardsSystem•64MB RAMControl Panel•LED ButtonSupported Platforms•Microsoft Windows 2000/2003/XPI/Vista/7, Mac OS, LinuxCommunication•USB, Ethernet (Option)Power Supply•Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)•48WTemperature / Humidity•15~35 °C / 20~80%Dimensions•172 mm x 377mm x 190mmWeight•3.4 kg / 7.5 lbsEncoding Options•ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard•ISO 7816 (ID -1)Contactless Smartcard•ISO 15693, DESFIRE, iCLASS	ҮМСКО		28 sec. (128 cards/hour)
Output Hooper25 cardsSystemMemory64MB RAMControl PanelLED ButtonSupported PlatformsMicrosoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunicationUSB, Ethernet (Option)Power SupplyFree Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)48WTemperature / Humidity15~35 °C / 20~80%DimensionsIT2 mm x 377mm x 190mmWeight3.4 kg / 7.5 lbsEncoding OptionsISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardISO 15693, DESFIRE, iCLASS	Capacity		
SystemMemory•64MB RAMControl Panel•LED ButtonSupported Platforms•Microsoft Windows 2000/2003/XPI/Vista/7, Mac OS, LinuxCommunication•USB, Ethernet (Option)Power Supply•Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)•48WTemperature / Humidity•15~35 °C / 20~80%Dimensions•172 mm x 377mm x 190mmWeight•3.4 kg / 7.5 lbsEncoding Options•ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard•ISO 7816 (ID -1)Contactless Smartcard•MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Input Hooper		80 cards
Memory•64MB RAMControl Panel•LED ButtonSupported Platforms•Microsoft Windows 2000/2003/XPI/Vista/7, Mac OS, LinuxCommunication•USB, Ethernet (Option)Power Supply•Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)•48WTemperature / Humidity•15~35 °C / 20~80%Dimensions172 mm x 377mm x 190mmWeight•3.4 kg / 7.5 lbsEncoding OptionsMagnetic•ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard•ISO 7816 (ID -1)Contactless Smartcard•MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Output Hooper		25 cards
Control Panel• LED ButtonSupported Platforms• Microsoft Windows 2000/2003/XPI/Vista/7, Mac OS, LinuxCommunication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• ISO 7816 (ID -1)(Internal & External)ISO 15693, DESFIRE, iCLASS	System		
Supported Platforms• Microsoft Windows 2000/2003/XP/Vista/7, Mac OS, LinuxCommunication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• ISO 7816 (ID -1)(Internal & External)ISO 15693, DESFIRE, iCLASS	Memory		64MB RAM
Mac OS, LinuxCommunication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Control Panel		LED Button
Communication• USB, Ethernet (Option)Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions• 172 mm x 377mm x 190mmDimension (W x L x H)• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Supported Platforms		Microsoft Windows 2000/2003/XP/Vista/7,
Power Supply• Free Voltage (AC 110/220V, 50~60Hz)Power Consumption (Max)• 48WTemperature / Humidity• 15~35 °C / 20~80%Dimensions• 172 mm x 377mm x 190mmDimension (W x L x H)• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS			Mac OS, Linux
Power Consumption (Max)48WTemperature / Humidity15~35 °C / 20~80%DimensionsDimension (W x L x H)172 mm x 377mm x 190mmWeight3.4 kg / 7.5 lbsEncoding OptionsMagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Communication		USB, Ethernet (Option)
Temperature / Humidity• 15~35 °C / 20~80%DimensionsDimension (W x L x H)• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding OptionsMagnetic• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Power Supply		Free Voltage (AC 110/220V, 50~60Hz)
DimensionsDimension (W x L x H)• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding OptionsMagnetic• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Power Consumption (Max)		48W
Dimension (W x L x H)• 172 mm x 377mm x 190mmWeight• 3.4 kg / 7.5 lbsEncoding Options Magnetic• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard• ISO 7816 (ID -1)Contactless Smartcard• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Temperature / Humidity		15~35 °C / 20~80%
Weight Encoding Options Magnetic• 3.4 kg / 7.5 lbsMagnetic• ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact Smartcard Contactless Smartcard• ISO 7816 (ID -1)Contactless Smartcard (Internal & External)• MIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Dimensions		
Encoding Options • ISO 7811 (Track I, II, III Read / Write), Magnetic • ISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS II • ISO 7816 (ID -1) Contact Smartcard • ISO 7816 (ID -1) Contactless Smartcard • MIFARE, ISO 14443 (Type A / B), (Internal & External) ISO 15693, DESFIRE, iCLASS	Dimension (W x L x H)		172 mm x 377mm x 190mm
MagneticISO 7811 (Track I, II, III Read / Write), HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B), ISO 15693, DESFIRE, iCLASS	Weight		3.4 kg / 7.5 lbs
HiCo/LoCo, JIS IIContact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B),(Internal & External)ISO 15693, DESFIRE, iCLASS	Encoding Options		
Contact SmartcardISO 7816 (ID -1)Contactless SmartcardMIFARE, ISO 14443 (Type A / B),(Internal & External)ISO 15693, DESFIRE, iCLASS	Magnetic		ISO 7811 (Track I, II, III Read / Write),
Contactless SmartcardMIFARE, ISO 14443 (Type A / B),(Internal & External)ISO 15693, DESFIRE, iCLASS			HiCo/LoCo, JIS II
(Internal & External) ISO 15693, DESFIRE, iCLASS	Contact Smartcard		ISO 7816 (ID -1)
	Contactless Smartcard		MIFARE, ISO 14443 (Type A / B),
Cortifications CE ECC KCC	(Internal & External)		ISO 15693, DESFIRE, iCLASS
	Certifications		CE, FCC, KCC

Laminex-ID Systems Singapore Pte Ltd (Co. Reg. No.: 200610058H)

10 Ubi Crescent, #07-38/39 Ubi Techpark, Singapore 408564 Tel : (65) 6742 2423 Fax : (65) 6742 2426 Email: laminex@singnet.com.sg Laminex-ID Systems Sdn. Bhd. (Co. Reg. No.: 368789M) 64, Jalan Permas 9/12, Bandar Baru Permas Jaya 81750 Masai, Johor, Malaysia Tel : (60)-7-3864570 Fax : (60)-7-3864571 Email: laminexid@unifi.my Smart, Smarter than any other ID Card Printer

12

SMART-30S is value for everyone



WWW.SMARTIDCARDPRINTER.COM